De 3-31-87

DOW CORNING CORPORATION MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 90-006 - 2 CATALYST EMERGENCY TELEPHONE NO. (517) 496-5900

SECTION I - GENERAL INFORMATION

MANUFACTURERS NAME: DOW CORNING CORPORATION ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): NONE D.O.T. HAZARD NAME(49CFR 172.101): NONE D.O.T. ID NO(49CFR 172.101): NONE

D.O.T. HAZARD CLASS(49CFR 172.101): NONE

RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): EP TOXIC-CHROMIUM (D007)

E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): CHROMIUM

NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704 HEALTH (NFPA): 2 FLAMMABILITY (NFPA): 1

HEALTH (NFPA): 2 CAS NO: MIXTURE REACTIVITY (NFPA): 0 DOW CORNING WARNING CODE: 37

GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENT

DIBUTYLTIN-2-ETHYLHEXOATE % 3 TIV % 3 % 5 TLV (UNITS): 0.1MG/M3; PELSAME CHROMIUM TRIOXIDE (CHROME OXIDE) TLV (UNITS): 0.5MG/M3;PELSAME

ONLY THOSE INGREDIENTS LISTED IN THIS SECTION HAVE BEEN DETERMINED TO BE HAZARDOUS AS DEFINED IN 29 CFR 1910.1200. AN INGREDIENT MARKED WITH AN ASTERISK(*) IS ALSO LISTED IN 29 CFR 1910.1200(D) #4 AS KNOWN OR SUSPECTED CARCINOGEN.

COMMENT: TLV BASED ON TIN (ORGANIC COMPOUND) AND CHROMIUM (SOLUBLE CHROMIC SALT).

MATL NAME: DOW CORNING(R) 90-006 - 2 CATALYST

SECTION III - EFFECTS OF OVEREXPOSURE

EYES: MAY IRRITATE SERIOUSLY WITH MODERATE CORNEAL INJURY AND CONSIDERABLE REDNESS LASTING A WEEK OR MORE.

SKIN: A SINGLE EXPOSURE FOR SEVERAL HOURS MAY CAUSE SLIGHT REDDENING. LONGER OR REPEATED CONTACTS MAY CAUSE MODERATE IRRITATION AND POSSIBLY A MILD BURN.

INHALATION: NO IRRITATION TO NOSE OR THROAT EXPECTED. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE.

ORAL: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, ETC., DURING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY. SWALLOWING SUBSTANTIAL AMOUNTS MAY CAUSE SOME INJURY.

COMMENT: ANIMAL TESTS HAVE SHOWN CHROME OXIDE TO CAUSE CANCER AFTER PROLONGED OVEREXPOSURES

THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER FOR 15 MINUTES. OBTAIN IMMEDIATE MEDICAL ATTENTION.

SKIN: WIPE OFF AND FLUSH WITH WATER. OBTAIN MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PESISTS.

INHALATION: NO PROBLEM.

ORAL: NO PROBLEM.

COMMENT: NONE.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250°F/121°C AUTOIGNITION: NOT DETERMINED FLAMMABILITY LIMITS IN AIR : LOWER: NA UPPER: NA

WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF_CONTAINED BREATHING APPRARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN TO DOW CORNING.

COMMENTS: NA=NOT APPLICALBE.

EXTINGUISHING MEDIA: WATER

SECTION VI - PHYSICAL DATA

BOILING POINT(@ 760 MM HG): ABOVE 300°F/149°C. SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.1 MELTING POINT: NOT APPLICABLE
VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM.
VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): NOT APPLICABLE PERCENT VOLATILE BY VOLUME (%): LESS THAN 5% EVAPORATION RATE (ETHER = 1): LESS THAN 1 SOLUBILITY IN WATER(%): LESS THAN 0.1% ODOR, APPEARANCE, COLOR: VERY LITTLE ODOR, PASTE-LIKE, GREEN

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS

DOW CORNING CORPORATION

MATL NAME: DOW CORNING(R) 90-006 - 2 CATALYST

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATABILITY(MATERIAL TO: AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.

CONDITIONS TO AVOID: NOT APPLICABLE

HAZARDOUS DECOMPOSITION PRODUCTS: METAL OXIDES, SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE

COMMENTS: NONE

SECTION VIII - SPILL, LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

PROTECTIVE EQUIPMENT:

EYES: USE CHEMICAL WORKER GOGGLES.

SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: NONE

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

VENTILATION:

LOCAL EXHAUST: NONE

MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: NONE SHOULD BE NEEDED.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING, USE AT ELEVATED TEMPERATURE MAY REQUIRE ADDED PRECAUTIONS.

* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING. COMMENTS: NONE

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 90°F/32°C. USE REASONABLE CARE.

OTHER PRECAUTIONS: NONE KNOWN TO DOW CORNING.
COMMENTS: TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY
FORM AT TEMPERATURES ABOVE 150 C IN THE PRESENCE OF AIR. PROVIDE ADEQUATE
VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

DOW CORNING CORPORATION MATL NAME: DOW CORNING(R) 90-006 - 2 CATALYST

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER LAST REVISION DATE: OCTOBER 15, 1985 PREVIOUS REVISION DATE: MAY 27, 1981 DATE: NOVEMBER 07, 1985

(R) INDICATES REGISTERED OF TRADEMARK OF THE DOW CORNING CORPORATION.